

5GHz 300Mbps Outdoor High Gain Wireless TDMA CPE / ROUTER

WIS-Q5300L

5 GHz

WID™

TDMA protocol

16dBi

dual-pola antenna




Product Overview

WIS-Q5300L is a 5GHz 300Mbps 2x2 MIMO outdoor wireless CPE based on 802.11a/n technology. It is high performance, cost-effective and dedicated to long distance wireless network solutions. Featuring the revolutionary WisOS technology in firmware design and 16dBi directional dual-polarized antenna, WIS-Q5300L is specialized designed for rural Internet access, long distance wireless data transmission, wireless coverage extension and other industrial wireless solutions.

Features and Benefits

- Compliant with 802.11n/a, speed up to 300Mbps
- WiD TDMA greatly improves the network scalability in throughput and latency
- Multi-operation modes support Gateway/WISP/Client/Access Point/Repeater
- 16dBi dual-polarized antenna to build long distance Wi-Fi connection
- Passive POE(24VDC) for flexible deployment
- Supports RSSI signal LEDs
- Transmit power selectable and distance control
- Supports QoS: Traffic Control & WMM
- Supports MAC & IP Address Filter
- Supports WiController SNMP, Remote Management
- IP65 outdoor Weather-proof housing

Network Example



The WIS-Q5300L as a station in PtMP WISP connection.

Specification

> Radio

- 802.11a/n radio (Atheros 600MHz)
 - Speed up to 300 Mbps
 - Frequency Range: 5.150-5.250GHz
 - 5.250-5.350GHz (Support DFS)
 - 5.470-5.725GHz (Support DFS)
 - 5.725-5.825GHz
 - Tx Power up to 23dBm
 - Rx Sensitivity 300M: -74dBm@10% PER
 - 54M: -78dBm@10% PER
 - 1M: -98dBm@10% PER
-

> Antenna

- 16dBi dual-polarized directional antenna
 - Beamwidth(HPBW) Horizontal: 45°, Vertical: 14°
 - Open space up to 1~10km (dependent)
-

>Physical Parameters

- Dimension: 200*90*68mm
 - Weight: 0.27kg
 - Enclosure: Weatherproof Plastic
 - ESD Protection: 15kV
 - Lightning Protection: 4kV
 - Working Temp: -40 ~ 65°C
 - Storage Temp: -40 ~85°C
 - Working Humidity: 10%~95% non-condensing
-

> Security

- Integrated Firewall
- WPA/WPA2;WPA-PSK/WPA2-PSK (AES/TKIP) Encryption; 64/128-bit WEP;

> Interfaces

- 1x10/100 Base-T Ethernet (RJ45 with Passive PoE)
 - Reset
-

>Power

- 24VDC, 0.75A
 - Power Consumption: 6W
-

>LED

- Power:On/Off
 - LAN:On/Off/Flashing
 - WLAN:On/Off/Flashing
 - RSSI Signal: 1,2,3
-

>Warranty

- 2 Years
-

>Certification

- CE, RoHS
-

>Package content

- WIS-Q5300L
- Quick Setup Guide
- Power Adapter with Passive PoE
- Mounting kits