

# 2.4GHz 300Mbps Hi-Gain Outdoor Wireless WISP CPE

# **WIS-Q2300L**



**TDMA protocol** 



dual-pola antenna





# **Product Overview**

WIS-Q2300L is a high gain outdoor wireless access point and CPE based on 802.11b/g/n technology. It is high performance, cost-effective and dedicated to long distance wireless network solutions. Featuring the 2\*2 MIMO technology in hardware and 12dBi directional dual-polarized antenna, WIS-Q2300L is specialized designed for rural Internet access, long distance wireless data transmission, wireless coverage extension and other industrial wireless solutions.

# **Features and Benefits**

- WiD TDMA greatly improves the network scalability in throughput and latency
- Multi-operation modes support WISP and bridge station mode
- 12dBi dual-polarized antenna to build long distance Wi-Fi connection
- Passive POE(24VDC) for flexible deployment
- Supports site survey and RSSI signal LEDs
- IP65 outdoor weather-proof housing selectable
- OEM/ODM, customized enclosure and label available

# **Network Example**



The WIS-Q2300L as clients in PtMP WISP connection for home and enterprise users.

# **Specification**

#### > Radio

- 802.11b/g/n radio (Atheros 600MHz)
- Speed up to 300 Mbps
- Frequency Range: 2.4-2.4835GHz
- Tx Power up to 20dBm
- Rx Sensitivity 300M: -73dBm@10% PER

54M: -78dBm@10% PER 1M: -98dBm@10% PER

#### > Antenna

- 12dBi dual-polarized directional antenna
- Beamwidth(HPBW): Horizontal: 60°, Vertical: 30°
- Open space up to 1~5km (dependent)

## >Physical Parameters

- Dimension: 269\*47\*119mm

- Wight: 0.4kg

- Enclosure: Weatherproof Plastic

- ESD Protection: 15kV

- Working Temp: -20 ~ 65°C

- Storage Temp: -40 ~85°C

- Working Humidity: 10%~95% non-condensing

### > Interfaces

- 1x 10/100Base-T Ethernet (RJ45 with Passive PoE)
- Reset

#### > Power

- 24VDC, 0.5A
- Power Consuption: 4W

### >Security

- Integrated Firewall
- WPA/WPA2;WPA-PSK/WPA2-PSK (AES/TKIP) Encryption; 64/128-bit WEP;

#### >LED

- Power:On/Off
- LAN:On/Off/Flashing
- WLAN:On/Off/Flashing
- RSSI Signal: 1,2,3

### >Warranty

- 1 Year

### >Certification

- CE, RoHS

## >Package content

- WIS-Q2300L
- Quick Setup Guide
- Power Adapter with Passive PoE
- Mounting kits